Clip, 10.3 x 38 mm, 20A (UL)



Technical Data Fuse-Link

20 A (UL)	See below: Approvals and Compliances
Description - Through hole mounting	Applications - Combiner Boxes in Photovoltaic Systems
	References Fuseholder to ASO 10.3x38
	Weblinks pdf data sheet, html datasheet, General Product Information, Distributor-

Stock-Check, Detailed request for product, Microsite

Wave

10.3 x 38 mm Soldering Methods Mounting PCB Soldering Profile Solderability 235 °C / 2 sec acc. to IEC 60068-2-20, Terminal Solder THT Test Ta, method 1 Rated current 20A (UL) Resistance to Soldering Heat 260 °C / 10 sec acc. to IEC 60068-2-20, Degree of Protection IP00 Test Tb, method 1A Material: Terminals see variants Contact Resistance < mΩ at 100 mA Unit Weight 4.1 g Storage Conditions 0°C to 60°C, max. 70% r.h. Product Marking **(**, Type, Certification marks

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 231660

-

231660

Application standards


Application standards where the product can be used

Organization	Design	Standard	Description				
IEC	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements				
Compliances							
The product comp	blies with following Guide Lines						

	till following dalad Einoo		
Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimension [mm]

______ 12 mm







Drilling diagram

All Variants

Clip	Terminal	Material: Terminals	Order Number	
•	straight	Tin-Plated Bronze	7170.0470	

Most Popular.

Availability for all products can be searched real-time: https://www.schurter. com/en/info-center/support-tools/stock-check-distributors

Packaging Unit

Bulk (50 pcs.)